

200-355 - WIFUND Implementing Cisco Wireless Network Fundamentals

<http://www.certleader.com/200-355-dumps.html>



1. When a guest client is authenticated, which type of connection is created between the controller-based AP and the client?

- A. as SSL connection
- B. a TLS encrypted tunnel
- C. an unsecured connection
- D. a 802.1x/EAP tunnel
- E. an IPsec tunnel

Answer: C

2. Which interface is considered a dynamic interface?

- A. the virtual interface
- B. the AP manager interface
- C. the LAG interface
- D. the management interface
- E. the service port interface
- F. a WLAN client data interface

Answer: F

3. The introduction of consumer phones and tablets into enterprise WLANs can have an impact on 802.11a/b/g/n deployments. The Apple iPhone 4 and iPad 2 are very common examples.

Which statement best describes the abilities of these devices?

- A. The Apple iPhone 4 and the iPad 2 use 2.4 GHz and 5 GHz. The Apple iPhone 4 uses only one spatial stream and the iPad 2 uses two spatial streams.
- B. The Apple iPhone 4 uses only 2.4 GHz and the iPad 2 only uses 5 GHz. The Apple iPhone 4 uses only one spatial stream and the iPad 2 uses two spatial streams.

C. The Apple iPhone 4 uses 2.4 GHz and the iPad 2 uses 2.4 GHz or 5 GHz. The Apple iPhone 4 only uses one spatial stream and the iPad 2 uses two spatial streams.

D. The Apple iPhone 4 uses 2.4 GHz and the iPad 2 uses 2.4 GHz or 5 GHz. The Apple iPhone 4 and the iPad 2 use only one spatial stream.

Answer: D

4. Which user group has the ability to configure all features of the Cisco WCS except the user accounts and passwords?

A. Admin

B. SuperUser

C. Root

D. Supervisor

Answer: A

5. What is the maximum number of lightweight APs that can be supported from a single Cisco WCS Navigator management console with Cisco WCS and Cisco WLC running version 7.0 code?

A. 10,000

B. 20,000

C. 25,000

D. 30,000

E. 60,000

Answer: D

6. Which two Cisco WLC management-access methods are available as the default setting?

(Choose two.)

- A. SSH
- B. HTTPS
- C. Telnet
- D. HTTP

Answer: A,B

7. An engineer recently removed a WLC from a WCS, but the APs associated to the WLC are still showing on the WCS. What is a reason for this?

- A. The associated APs must be removed manually.
- B. The APs must be removed from the WCS map.
- C. The hold-down timer must expire before the APs will be removed.
- D. The APs must be audited.

Answer: A

8. Which three items are allowed on an Ethernet trunk port? (Choose three.)

- A. autonomous AP
- B. FlexConnect AP
- C. local AP
- D. monitor AP
- E. rogue detector AP
- F. sniffer AP
- G. SE-Connect AP
- H. Cisco WLC

Answer: A,B,E

9. Which portion of a WLAN deployment can WLC message logs help to troubleshoot?

- A. RF issues
- B. encryption issues between APs and clients
- C. configuration verification issues
- D. infrastructure and client Issues
- E. AP placement issues

Answer: D

10. An engineer wants to set up guest wireless that requires users to log in via a splash page prior to accessing the network. Which authentication method should be configured?

- A. LDAP
- B. RADIUS
- C. local authentication
- D. WebAuth
- E. PSK

Answer: D

11. A Cisco WCS administrator has marked an alarm as acknowledged. For how many days does Cisco WCS prevent the alarm from reappearing, even if the source of the alarm reoccurs?

- A. 1
- B. 7
- C. 10
- D. 30

Answer: B

12. What is the EIRP value for a transmitter that has a transmitter capable of 15 dBm, an

antenna that has a gain of 12 dBi, and a cable that connects the transmitter to the antenna that has 1 db loss?

- A. 26 dBm
- B. 100 mW
- C. .86 dBm
- D. 165 dBm
- E. 1000 mW

Answer: A

13. A controller is connected to a Cisco Catalyst switch. The switch port configuration looks like this:

```
interface GigabitEthernet 1/0/10
switchport
switchport trunk encapsulation dot1q
switchport trunk allowed vlan 1,20,30,50
switchport trunk native vlan 20
switchport mode trunk
```

Which controller CLI command assigns its management interface to the native VLAN interface of the Cisco Catalyst switch?

- A. config interface vlan management 0
- B. config interface vlan management 1
- C. config interface vlan management 20
- D. config interface vlan management 30
- E. config interface vlan management 50

Answer: A

14. Which two services require an RToWLAN design? (Choose two.)

- A. WVoIP
- B. video conferencing
- C. multicast video
- D. Telnet
- E. SSH

Answer: A,B

15. A customer has asked for its wireless equipment to be managed as securely as possible.

Which three management protocols will provide encrypted access to the equipment?

(Choose three.)

- A. Secure Shell
- B. HTTPS
- C. SNMPv3
- D. Telnet
- E. SNMPv2c
- F. HTTP

Answer: A,B,C

16. What is an interferer that an engineer may see in Cisco CleanAir?

- A. microwave ovens
- B. rogue APs
- C. malicious clients
- D. co-channel interference

Answer: A

17. You are in a coffee shop and you have connected to their wireless hot-spot. Your Windows 7 wireless client shows five green bars with a yellow shield.

Which statement about the level of signal strength and the WLAN security that is present is true?

- A. You have excellent signal strength and a secure network connection.
- B. Your wireless client needs a username and password before it can connect to the WLAN.
- C. You have excellent signal strength and the client is waiting for you to enter a username and password.
- D. Your laptop is not receiving a signal.
- E. Your laptop is receiving an excellent signal and the network security is open.

Answer: E

18. A network engineer at a retail store needs a wireless deployment that can be easily maintained and verified for PCI compliance. What solution will meet this need with the least work?

- A. Cloud
- B. Autonomous
- C. FlexConnect
- D. Centralized

Answer: A

19. Which action secures the SNMPv2C protocol in a Cisco WLC?

- A. configure new communities and disable default communities
- B. use digital certificates to authenticate and encrypt transmissions
- C. enable password or transfer encryption

D. set a username and difficult-to-guess password

Answer: A

20. Which three options relate to event-driven RRM? (Choose three.)

A. any 802.11n AP models

B. specific AP models

C. minimum of AP and WLC

D. minimum of AP, WLC, and WCS

E. minimum of AP, WLC, WCS, and MSE

F. configurable in WLC at 802.11b/g/n > RRM > TPC

G. configurable in WLC at 802.11b/g/n > RRM > DCA

Answer: B,C,G

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 200-355 Exam with Our Prep Materials Via below:

<http://www.certleader.com/200-355-dumps.html>