


# AWS-SysOps - AWS Certified SysOps Administrator Associate

<http://www.certleader.com/AWS-SysOps-dumps.html>



1. - (Topic 2)

A user is running one instance for only 3 hours every day. The user wants to save some cost with the instance. Which of the below mentioned Reserved Instance categories is advised in this case?

- A. The user should not use RI; instead only go with the on-demand pricing
- B. The user should use the AWS high utilized RI
- C. The user should use the AWS medium utilized RI
- D. The user should use the AWS low utilized RI

**Answer: A**

Explanation:

The AWS Reserved Instance provides the user with an option to save some money by paying a one-time fixed amount and then save on the hourly rate. It is advisable that if the user is having 30% or more usage of an instance per day, he should go for a RI. If the user is going to use an EC2 instance for more than 2200-2500 hours per year, RI will help the user save some cost. Here, the instance is not going to run for less than 1500 hours. Thus, it is advisable that the user should use the on-demand pricing.

2. - (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/24. The user has created a public subnet with CIDR 20.0.0.0/25. The user is trying to create the private subnet with CIDR 20.0.0.128/25. Which of the below mentioned statements is true in this scenario?

- A. It will not allow the user to create the private subnet due to a CIDR overlap
- B. It will allow the user to create a private subnet with CIDR as 20.0.0.128/25
- C. This statement is wrong as AWS does not allow CIDR 20.0.0.0/25
- D. It will not allow the user to create a private subnet due to a wrong CIDR range

**Answer: B**

Explanation:

When the user creates a subnet in VPC, he specifies the CIDR block for the subnet. The CIDR block of a subnet can be the same as the CIDR block for the VPC (for a single subnet in the VPC., or a subset (to enable multiple subnets.. If the user creates more than one subnet in a VPC, the CIDR blocks of the subnets must not overlap. Thus, in this case the user has created a VPC with the CIDR block 20.0.0.0/24, which supports 256 IP addresses (20.0.0.0 to 20.0.0.255.. The user can break this CIDR block into two subnets, each supporting 128 IP addresses. One subnet uses the CIDR block 20.0.0.0/25 (for addresses 20.0.0.0 - 20.0.0.127. and the other uses the CIDR block 20.0.0.128/25 (for addresses 20.0.0.128 - 20.0.0.255..

3. - (Topic 2)

A user has configured Elastic Load Balancing by enabling a Secure Socket Layer (SSL) negotiation configuration known as a Security Policy. Which of the below mentioned options is not part of this secure policy while negotiating the SSL connection between the user and the client?

- A. SSL Protocols
- B. Client Order Preference
- C. SSL Ciphers
- D. Server Order Preference

**Answer: B**

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. A security policy is a combination of SSL Protocols, SSL Ciphers, and the Server Order Preference option.

4. - (Topic 2)

An organization has setup consolidated billing with 3 different AWS accounts. Which of the below mentioned advantages will organization receive in terms of the AWS pricing?

- A. The consolidated billing does not bring any cost advantage for the organization
- B. All AWS accounts will be charged for S3 storage by combining the total storage of each account
- C. The EC2 instances of each account will receive a total of 750\*3 micro instance hours free
- D. The free usage tier for all the 3 accounts will be 3 years and not a single year

**Answer: B**

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. For billing purposes, AWS treats all the accounts on the consolidated bill as one account. Some services, such as Amazon EC2 and Amazon S3 have volume pricing tiers across certain usage dimensions that give the user lower prices when he uses the service more.

5. - (Topic 2)

A user has setup connection draining with ELB to allow in-flight requests to continue while the instance is being deregistered through Auto Scaling. If the user has not specified the draining time, how long will ELB allow in-flight requests traffic to continue?

- A. 600 seconds
- B. 3600 seconds
- C. 300 seconds
- D. 0 seconds

**Answer: C**

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served. The user can specify a maximum time (3600 seconds) for the load balancer to keep the connections alive before reporting the instance as deregistered. If the user does not specify the maximum timeout period, by default, the load balancer will close the connections to the deregistering instance after 300 seconds.

6. - (Topic 2)

A user has created an S3 bucket which is not publicly accessible. The bucket is having thirty objects which are also private. If the user wants to make the objects public, how can he configure this with minimal efforts?

- A. The user should select all objects from the console and apply a single policy to mark them public
- B. The user can write a program which programmatically makes all objects public using S3 SDK
- C. Set the AWS bucket policy which marks all objects as public
- D. Make the bucket ACL as public so it will also mark all objects as public

**Answer: C**

Explanation:

A system admin can grant permission of the S3 objects or buckets to any user or make the objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket.

7. - (Topic 2)

A user is checking the CloudWatch metrics from the AWS console. The user notices that the CloudWatch data is coming in UTC. The user wants to convert the data to a local time zone. How can the user perform this?

- A. In the CloudWatch dashboard the user should set the local timezone so that CloudWatch shows the data only in the local time zone

B. In the CloudWatch console select the local timezone under the Time Range tab to view the data as per the local timezone

C. The CloudWatch data is always in UTC; the user has to manually convert the data

D. The user should have send the local timezone while uploading the data so that CloudWatch will show the data only in the local timezone

**Answer: B**

Explanation:

If the user is viewing the data inside the CloudWatch console, the console provides options to filter values either using the relative period, such as days/hours or using the Absolute tab where the user can provide data with a specific date and time. The console also provides the option to search using the local timezone under the time range caption in the console because the time range tab allows the user to change the time zone.

8. - (Topic 2)

A user has created a queue named “myqueue” with SQS. There are four messages published to queue which are not received by the consumer yet. If the user tries to delete the queue, what will happen?

A. A user can never delete a queue manually. AWS deletes it after 30 days of inactivity on queue

B. It will delete the queue

C. It will initiate the delete but wait for four days before deleting until all messages are deleted automatically.

D. It will ask user to delete the messages first

**Answer: B**

Explanation:

SQS allows the user to move data between distributed components of applications so they can perform different tasks without losing messages or requiring each component to be always available. The user can delete a queue at any time, whether it is empty or not. It is important to note that queues retain messages for a set period of time. By default, a queue retains messages for four days.

9. - (Topic 2)

A customer is using AWS for Dev and Test. The customer wants to setup the Dev environment with Cloudformation. Which of the below mentioned steps are not required while using Cloudformation?

A. Create a stack

B. Configure a service

C. Create and upload the template

D. Provide the parameters configured as part of the template

**Answer: B**

Explanation:

AWS CloudFormation is an application management tool which provides application modelling, deployment, configuration, management and related activities. AWS CloudFormation introduces two concepts: the template and the stack. The template is a JSON-format, text-based file that describes all the AWS resources required to deploy and run an application. The stack is a collection of AWS resources which are created and managed as a single unit when AWS CloudFormation instantiates a template. While creating a stack, the user uploads the template and provides the data for the parameters if required.

10. - (Topic 2)

A user has configured ELB with three instances. The user wants to achieve High Availability as well as redundancy with ELB. Which of the below mentioned AWS services helps the user achieve this for ELB?

A. Route 53

B. AWS Mechanical Turk

C. Auto Scaling

D. AWS EMR

**Answer: A**

Explanation:

The user can provide high availability and redundancy for applications running behind Elastic Load Balancer by enabling the Amazon Route 53 Domain Name System (DNS) failover for the load balancers. Amazon Route 53 is a DNS service that provides reliable routing to the user's infrastructure.

11. - (Topic 2)

A user has enabled the Multi AZ feature with the MS SQL RDS database server. Which of the below mentioned statements will help the user understand the Multi AZ feature better?

A. In a Multi AZ, AWS runs two DBs in parallel and copies the data asynchronously to the replica copy

B. In a Multi AZ, AWS runs two DBs in parallel and copies the data synchronously to the replica copy

C. In a Multi AZ, AWS runs just one DB but copies the data synchronously to the standby replica

D. AWS MS SQL does not support the Multi AZ feature

**Answer: C**

Explanation:

Amazon RDS provides high availability and failover support for DB instances using Multi-AZ deployments. In a Multi-AZ deployment, Amazon RDS automatically provisions and maintains a synchronous standby replica in a different Availability Zone. The primary DB instance is synchronously replicated across Availability Zones to a standby replica to provide data redundancy, eliminate I/O freezes, and minimize latency spikes during system backups. Running a DB instance with high availability can enhance availability during planned system maintenance, and help protect your databases against DB instance failure and Availability Zone disruption. Note that the high-availability feature is not a scaling solution for read-only scenarios; you cannot use a standby replica to serve read traffic. To service read-only traffic, you should use a read replica.

12. - (Topic 2)

An organization is setting up programmatic billing access for their AWS account. Which of

the below mentioned services is not required or enabled when the organization wants to use programmatic access?

- A. Programmatic access
- B. AWS bucket to hold the billing report
- C. AWS billing alerts
- D. Monthly Billing report

**Answer: C**

Explanation:

AWS provides an option to have programmatic access to billing. Programmatic Billing Access leverages the existing Amazon Simple Storage Service (Amazon S3) APIs. Thus, the user can build applications that reference his billing data from a CSV (comma-separated value) file stored in an Amazon S3 bucket. To enable programmatic access, the user has to first enable the monthly billing report. Then the user needs to provide an AWS bucket name where the billing CSV will be uploaded. The user should also enable the Programmatic access option.

13. - (Topic 2)

A user has stored data on an encrypted EBS volume. The user wants to share the data with his friend's AWS account. How can user achieve this?

- A. Create an AMI from the volume and share the AMI
- B. Copy the data to an unencrypted volume and then share
- C. Take a snapshot and share the snapshot with a friend
- D. If both the accounts are using the same encryption key then the user can share the volume directly

**Answer: B**

Explanation:

AWS EBS supports encryption of the volume. It also supports creating volumes from existing snapshots

provided the snapshots are created from encrypted volumes. If the user is having data on an encrypted volume and is trying to share it with others, he has to copy the data from the encrypted volume to a new unencrypted volume. Only then can the user share it as an encrypted volume data. Otherwise the snapshot cannot be shared.

14. - (Topic 2)

A user is planning to setup notifications on the RDS DB for a snapshot. Which of the below mentioned event categories is not supported by RDS for this snapshot source type?

- A. Backup
- B. Creation
- C. Deletion
- D. Restoration

**Answer: A**

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. Event categories for a snapshot source type include: Creation, Deletion, and Restoration. The Backup is a part of DB instance source type.

15. - (Topic 2)

A user has created a web application with Auto Scaling. The user is regularly monitoring the application and he observed that the traffic is highest on Thursday and Friday between 8 AM to 6 PM. What is the best solution to handle scaling in this case?

- A. Add a new instance manually by 8 AM Thursday and terminate the same by 6 PM Friday
- B. Schedule Auto Scaling to scale up by 8 AM Thursday and scale down after 6 PM on Friday
- C. Schedule a policy which may scale up every day at 8 AM and scales down by 6 PM
- D. Configure a batch process to add a instance by 8 AM and remove it by Friday 6 PM

**Answer: B**

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. In this case the load increases by Thursday and decreases by Friday. Thus, the user can setup the scaling activity based on the predictable traffic patterns of the web application using Auto Scaling scale by Schedule.

16. - (Topic 2)

A user has launched an EC2 instance. The user is planning to setup the CloudWatch alarm. Which of the below mentioned actions is not supported by the CloudWatch alarm?

- A. Notify the Auto Scaling launch config to scale up
- B. Send an SMS using SNS
- C. Notify the Auto Scaling group to scale down
- D. Stop the EC2 instance

**Answer: B**

Explanation:

A user can create a CloudWatch alarm that takes various actions when the alarm changes state. An alarm watches a single metric over the time period that the user has specified, and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The actions could be sending a notification to an Amazon Simple Notification Service topic (SMS, Email, and HTTP endpoint), notifying the Auto Scaling policy or changing the state of the instance to Stop/Terminate.

17. - (Topic 2)

A root account owner has created an S3 bucket testmycloud. The account owner wants to allow everyone to upload the objects as well as enforce that the person who uploaded the object should manage the permission of those objects. Which is the easiest way to achieve this?

- A. The root account owner should create a bucket policy which allows the IAM users to upload the object
- B. The root account owner should create the bucket policy which allows the other account owners to set the object policy of that bucket
- C. The root account should use ACL with the bucket to allow everyone to upload the object
- D. The root account should create the IAM users and provide them the permission to upload content to the bucket

**Answer: C**

Explanation:

Each AWS S3 bucket and object has an ACL (Access Control List) associated with it. An ACL is a list of

grants identifying the grantee and the permission granted. The user can use ACLs to grant basic read/write permissions to other AWS accounts. ACLs use an Amazon S3-specific XML schema. The user cannot grant permissions to other users in his account. ACLs are suitable for specific scenarios. For example, if a bucket owner allows other AWS accounts to upload objects, permissions to these objects can only be managed using the object ACL by the AWS account that owns the object.

18. - (Topic 2)

A user has configured ELB with two EBS backed EC2 instances. The user is trying to understand the DNS access and IP support for ELB. Which of the below mentioned statements may not help the user understand the IP mechanism supported by ELB?

- A. The client can connect over IPV4 or IPV6 using Dualstack
- B. ELB DNS supports both IPV4 and IPV6
- C. Communication between the load balancer and back-end instances is always through IPV4
- D. The ELB supports either IPV4 or IPV6 but not both

**Answer: D**

Explanation:

Elastic Load Balancing supports both Internet Protocol version 6 (IPv6) and Internet Protocol version 4 (IPv4). Clients can connect to the user's load balancer using either IPv4 or IPv6 (in EC2-Classic). However, communication between the load balancer and its back-end instances uses only IPv4. The user can use the Dualstack-prefixed DNS name to enable IPv6 support for communications between the client and the load balancers. Thus, the clients are able to access the load balancer using either IPv4 or IPv6 as their individual connectivity needs dictate.

19. - (Topic 2)

A user has setup a CloudWatch alarm on an EC2 action when the CPU utilization is above 75%. The alarm sends a notification to SNS on the alarm state. If the user wants to simulate the alarm action how can he achieve this?

- A. Run activities on the CPU such that its utilization reaches above 75%
- B. From the AWS console change the state to 'Alarm'
- C. The user can set the alarm state to 'Alarm' using CLI
- D. Run the SNS action manually

**Answer: C**

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs

one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can test an alarm by setting it to any state using the SetAlarmState API (mon-set-alarm-state command). This temporary state change lasts only until the next alarm comparison occurs.

20. - (Topic 2)

An organization has added 3 of his AWS accounts to consolidated billing. One of the AWS accounts has purchased a Reserved Instance (RI) of a small instance size in the US-East-1a zone. All other AWS accounts are running instances of a small size in the same zone. What will happen in this case for the RI pricing?

- A. Only the account that has purchased the RI will get the advantage of RI pricing
- B. One instance of a small size and running in the US-East-1a zone of each AWS account will get the benefit of RI pricing
- C. Any single instance from all the three accounts can get the benefit of AWS RI pricing if they are running in the same zone and are of the same size
- D. If there are more than one instances of a small size running across multiple accounts in the same zone no one will get the benefit of RI

**Answer: C**

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. For billing purposes, consolidated billing treats all the accounts on the consolidated bill as one account. This means that all accounts on a consolidated bill can receive the hourly cost benefit of the Amazon EC2 Reserved Instances purchased by any other account. In this case only one Reserved Instance has been purchased by one account. Thus, only a single instance from any of the accounts will get the advantage of RI. AWS will implement the blended rate for each instance if more than one instance is running concurrently.

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your AWS-SysOps Exam with Our Prep Materials Via below:**

<http://www.certleader.com/AWS-SysOps-dumps.html>